

Aerodynamic Rotor Combo consisting of Rotor 31-XT-BD-CHI28 and channel insert 28
Rotor spinning machines R 40, R 60 and R 66

RIETER

Aerodynamic Rotor Combo

For automatic rotor spinning

Your benefits:

- Reduced yarn breakage by up to 65%
- Increased productivity by up to 6%
- Constant IPI and yarn strength values
- Potential to replace rotor 33-XT-BD




Aerodynamic Rotor Combo with Optimized Spinning Performance

Increased rotor speed by using rotor with smaller diameter

Aerodynamic Rotor Combo increases production by up to 6%

The smaller rotor in combination with the channel insert 28 results in a higher rotor speed and thus in an increased productivity of up to 6%. Its increased sliding wall angle a) leads to better sliding behaviour of the fibres.

This setup also allows the processing of lower raw material qualities, resulting in the same yarn values as when higher raw material qualities are processed with the previous standard rotor.



The Aerodynamic Rotor Combo with increased sliding wall angle

Order details


The Aerodynamic Rotor Combo is available as package*:

Part Nr.	Description	Machine type	Bearing type
11226386	Rotor Combo 31-XT-BD-AE-CHI28	R 40	AERO
11226387	Rotor Combo 31-XT-BD-EC-CHI28	R 40	EC
11226388	Rotor Combo 31-XT-BD-AE1-CHI28	R 60/ R 66	AERO
11226389	Rotor Combo 31-XT-BD-EC1-CHI28	R 60/ R 66	EC

* The Aerodynamic Rotor Combo can only be used combined with the channel insert 28.


Reduction of yarn ends down

Raw Material 100% cotton weaving yarn



Constant clearer cuts

Raw Material 100% cotton weaving yarn



Rieter Machine Works Ltd.

Klosterstrasse 20
CH-8406 Winterthur
T +41 52 208 7171
F +41 52 208 7283
aftersales@rieter.com

Rieter India Private Ltd.

Gat No. 768/2, Village Wing
Shindewadi-Bhor Road
Taluka Khandala, District Satara
IN-Maharashtra 412 801
T +91 2169 664 141
F +91 2169 664 226

Rieter (China) Textile Instruments Co., Ltd.

390 West Hehai Road
Changzhou 213022, Jiangsu
P.R. China
T +86 519 8511 0675
F +86 519 8511 0673

The data and illustrations in this brochure and on the corresponding data carrier refer to the date of printing. Rieter reserves the right to make any necessary changes at any time and without special notice. Rieter systems and Rieter innovations are protected by patents.

3418-v2 en 2204